

SAP ABAP table /BEV3/CHCTBDGIOI {Customizing Conditions IN/OUT Design IN}

_BEV3_CHCTBDGIOI
<u>MANDT</u> [CLNT (3)]
<u>IODESIGN</u> [NUMC (4)]
<u>PRTYPIN</u> [NUMC (4)]
<u>PRINID</u> [NUMC (4)]

/BEV3/CHCTBDGIOI-IODESIGN = /BEV3/CHCBDGIOD-IODESIGN 0..N

_BEV3_CHCBDGIOD
<u>MANDT</u> [CLNT (3)]
<u>IODESIGN</u> [NUMC (4)]

/BEV3/CHCTBDGIOI-PRINID = /BEV3/CHCBDGPRIN-PRINID 0..N

_BEV3_CHCBDGPRIN
<u>MANDT</u> [CLNT (3)]
<u>PRTYPIN</u> [NUMC (4)]
<u>PRINID</u> [NUMC (4)]

/BEV3/CHCTBDGIOI-PRTYPIN = /BEV3/CHCBDGPTIN-PRTYPIN

_BEV3_CHCBDGPTIN
<u>MANDT</u> [CLNT (3)]
<u>PRTYPIN</u> [NUMC (4)]

/BEV3/CHCTBDGIOI-MANDT = T000-MANDT 0..N

T000
<u>MANDT</u> [CLNT (3)]