SAP ABAP table BEAC_SPF_R1 {Customizing of Settlement Profiles}

BEAC_SPF

MANDT [CLNT (3)]

APPLICATION [CHAR (4)]

SETTLE_PROF [CHAR (8)]

BEAC_SPF_R1-SETTLE_PROF = BEAC_SPF-APPLICATION

{0,1}

BEAC_SPF_R1

MANDT [CLNT (3)]

APPLICATION [CHAR (4)]

SETTLE_PROF [CHAR (8)]

STY_FINAL [CHAR (4)]

STY_PARTIAL [CHAR (4)]

STY_CORRECT [CHAR (4)]

STY_M_ACCRL [CHAR (4)]

SETT_CALENDAR [CHAR (2)]

1

1

BEAC_SPF_R1-STY_CORRECT = BEAC_STY-APPLICATION

0..N

BEAC_STY

MANDT [CLNT (3)]

APPLICATION [CHAR (4)]

SETTLE_TYPE [CHAR (4)]

BEAC_SPF_R1-STY_FINAL = BEAC_STY-APPLICATION

1

BEAC_SPF_R1-STY_M_ACCRL = BEAC_STY-APPLICATION

0..N

1

0..N

BEAC_SPF_R1-STY_PARTIAL = BEAC_STY-APPLICATION

1

0..N

1

BEAC_SPF_R1-APPLICATION = BEFM_APPL-APPL

BEFM_APPL

APPL [CHAR (4)]

0..N

1

BEAC_SPF_R1-SETT_CALENDAR = TFACD-IDENT

TFACD

IDENT [CHAR (2)]

1