SAP ABAP table CRMC_PARTNER_AS {Access Sequences}

CRMC_PARTNER_PFT

PARTNER_PFT [CHAR (4)]

CRMC_PARTNER_AS-ORIGIN = COMC_PARTNER_DOR-ORIGIN

COMC_PARTNER_DOR

ORIGIN [CHAR (16)]

0..N

CRMC_PARTNER_AS

CLIENT [CLNT (3)]

ACCESS_SEQUENCE [CHAR (4)]

BATCH_SEQUENCE [NUMC (4)]

ORIGIN [CHAR (16)]

PARTNER_FCT [CHAR (8)]

PARTNER_PFT [CHAR (4)]

PFT_SUBTYPE [CHAR (4)]

BP_FUNCTION [CHAR (4)]

ORIGIN_FCT [CHAR (8)]

ORIGIN_PFT [CHAR (4)]

ORIGIN_PFT_SUB [CHAR (4)]

CRMC_PARTNER_AS-ACCESS_SEQUENCE = CRMC_PARTNER_AD-ACCESS_SEQUENCE

CRMC_PARTNER_AD

CLIENT [CLNT (3)]

ACCESS_SEQUENCE [CHAR (4)]

1

0..N

1

CRMC_PARTNER_AS-ORIGIN_FCT = CRMC_PARTNER_FCT-PARTNER_FCT

CRMC_PARTNER_FCT

CLIENT [CLNT (3)]

PARTNER_FCT [CHAR (8)]

0..N

CRMC_PARTNER_AS-PARTNER_FCT = CRMC_PARTNER_FCT-PARTNER_FCT

0..N

0..N

CRMC_PARTNER_AS-ORIGIN_PFT_SUB = CRMC_PARTNER_PS-PFT_SUBTYPE

0..N

CRMC_PARTNER_PS

PFT_SUBTYPE [CHAR (4)]

0..N

CRMC_PARTNER_AS-PFT_SUBTYPE = CRMC_PARTNER_PS-PFT_SUBTYPE

0..N

0..N

CRMC_PARTNER_AS-BP_FUNCTION = TB912-PAFKT

TB912

CLIENT [CLNT (3)]

PAFKT [CHAR (4)]

0..N