SAP ABAP table T7PIQ_GB_DECLIST {UCASLINK : Decision List}

T7PIQ_GB_DECLIST-MANDT = T000-MANDT

T000

<u>MANDT</u> [CLNT (3)]

T7PIQ_GB_DECLIST-CHOICENR = T7PIQCHOICES-CHOICE_NO

T7PIQCHOICES

<u>*MANDT*</u> [CLNT (3)]

<u>CHOICE_NO</u> [NUMC (2)]

T7PIQ_GB_DECLIST

MANDT [CLNT (3)]

TRANSCODE [CHAR (2)]

CHOICENR [NUMC (2)]

DECISION [CHAR (1)]

CAMPUS [CHAR (1)]

ENTRY_POINT [CHAR (1)]

OFFER_LEVEL [CHAR (1)]

T7PIQ_GB_DECLIST-CAMPUS = T7PIQ_GB_CAMPUSM-CAMPUS

T7PIQ_GB_CAMPUSM

<u>*MANDT*</u> [CLNT (3)]

<u>CAMPUS</u> [CHAR (1)]

T7PIQ_GB_DECLIST-DECISION = T7PIQ_GB_DECIS-DECISION

T7PIQ_GB_DECIS

T7PIQ_GB_DECLIST-ENTRY_POINT = T7PIQ_GB_ENT_PN-POINT_OF_ENTRY

<u>DECISION</u> [CHAR (1)]

T7PIQ_GB_ENT_PN

<u>*MANDT*</u> [CLNT (3)]

<u>POINT_OF_ENTRY</u> [CHAR (1)]

T7PIQ_GB_DECLIST-OFFER_LEVEL = T7PIQ_GB_OFFRLEV-OFFER_LEVEL

T7PIQ_GB_OFFRLEV

<u>*MANDT*</u> [CLNT (3)]

<u>OFFER_LEVEL</u> [CHAR (1)]

T7PIQ_GB_DECLIST-TRANSCODE = T7PIQ_GB_TRANS-UCAS_TRANSACTION

T7PIQ_GB_TRANS

<u>UCAS_TRANSACTION</u> [CHAR (2)]

1

1

1

0..N

1

0..N

1

0..N

0..N

0..N

0..N

0..N

0..N